SENSORS & SOFTWARE
from RADIODETECTION

LMX200™

Utility locating with GPR made simple



LMX200™ helps you to locate and map utilities with confidence.

SPX TECHNOLOGIES

Rapidly locate metallic and non-metallic utilities.



LMX200 GPR complements traditional pipe and cable locators, helping locate and map underground targets, including:

- Metallic pipes and cables
- Non-metallic pipes (PVC and asbestos cement)
- Storm and sewer systems
- Utilities with failed tracer wires
- Underground storage tanks and drainage tiles
- Septic system components
- Vaults, foundation walls, and concrete pads

System Features

Intuitive All-Weather Display
Rugged touchscreen with simple field workflows.

Geo-Referenced Results
Internal GNSS for screenshots and collected grids.

Built for Real-World Terrain
Lightweight cart with integrated odometer.

Simple Power Management
One battery powers the display, sensor and optional GNSS.

Depth & Resolution Balance
250 MHz UWB antenna balances depth penetration (up to 8 m / 26 ft) and resolution.




Field-to-Map Connectivity
Send marked targets directly to supported mapping applications.

Field Reporting
Automatic PDF Report of screenshots and interpretations.

High-Accuracy* Positioning
Optional external GNSS for visualization, mapping and processing.


Collect, Interpret & Map

Designed for efficient, confident field work



No complex collection settings, press Start and push the cart.

- DynaQ automatic stacking improves data quality.
- Easy hyperbola-fitting enables more accurate depth measurements.



Identify buried features and use the backup arrow to mark the ground or touch the screen to add digital interpretations.



Add & Visualize Interpretations in SplitView™

Trace buried linear features with confidence.

Map Findings in the Field

Wirelessly send marked targets to supported mapping applications.



External GNSS receiver required for Mapping and SplitView features

Professional Deliverables


PDF
Customer-Ready Reports
Automated PDF reports with interpretations and screenshots.


CSV
Flexible Data Export
Export georeferenced flags and interpretations for use in supported third-party applications.


KMZ
Visual Project Deliverables
Share Line Scan depth slices, interpretations and screenshots in Google Earth™.

Visualize More Underground

- Generate in-field depth slices
- Peel back underground layers
- Visualize utilities at multiple depths









1. Collect data your preferred way

Use guided grid collection or use GNSS-positioned survey lines without traditional grid setup.




2. Process depth slices in the field

Generate and review depth slices from grids or GNSS-positioned lines while on site.



3. Correlate depth slices to GPR data

Correlate the depth slice to the GPR cross-section to aid target interpretation.



4. Visualize your entire GPR survey

View collection path, depth slices and interpretations together while still in the field.

LMX-SG BUNDLES:
PLUG. PLAY. PRECISE.




LMX-SG bundles provide an out-of-the-box solution to integrate high-accuracy GNSS positioning into your LMX200 data. Every package includes a pre-configured Juniper Systems® Geode™ GNSS with connectivity, setup, and battery management—all taken care of at the system level for a seamless workflow.




ACCURATE POSITIONING | OUT-OF-THE-BOX SOLUTION | BATTERY MANAGEMENT | SYSTEM-LEVEL INTEGRATION

EKKO_Project™ Software

Visualize, Understand and Report your GPR results with the optional EKKO_Project PC Software









Core


Organize your GPR data, photos and other files and save as a single project file. Easily create PDF reports of your findings.



Examine (Cross-sections)



Reveal (Depth Slices)



3D Reveal (3D Visualization)

Specifications

Weight & Dimensions	
Size: 100 x 70 x 115 cm (39.4 x 27.6 x 45.3 in)	
Weight: 22 kg (48 lbs)	
Display Unit size: 21 cm (8 in) diagonal	
Power	
12 volt sealed lead acid gel cell	
Battery Capacity: 9.0 Ah	Battery Weight: 3.6 kg (7.9 lbs)
Battery Life: 4-6 hours	Charger: 110-240V

Environmental & Temperatures	
Ruggedized, environmentally sealed unit and connections	
IP65	Operating temperature range: -20°C to +50°C (-4°F to 122°F)
Regulatory Specifications	
Meets FCC 15.509, IC RSS-220 and ETSI EN-302066	
Data Storage	**Depth**
380 km (236 miles) of data	Up to 8 meters (26 feet)

Useful resources to make the most of your LMX:

- LMX200 training videos
- Utility Locating with GPR (Nulca-accredited) interactive and online course (SensoftU.com)
- Webinars and free online resources
- Learn more about our training offerings

Our Locations



USA

Raymond, ME
Kearneysville, WV

Canada

Mississauga, ON

Europe

United Kingdom **HQ**
France
Germany
The Netherlands

Asia Pacific

India
Hong Kong
Australia

Visit: **www.sensoft.ca** Follow us on:

Copyright © 2026 Radiodetection Ltd. All Rights Reserved. Radiodetection is a subsidiary of SPX Technologies, Inc. Sensors & Software, LMX, LMX200, DynaQ, DynaT, EKKO_Project and SplitView are either trademarks or registered trademarks of Radiodetection in the United States and / or other countries. Due to a policy of continued development, we reserve the right to alter or amend any published specification without notice. The image of the Geode is courtesy of Juniper Systems, Inc. Geode and Juniper Systems are trademarks of Juniper Systems, Inc. Used with permission. The image of PointMan is courtesy of PROSTAR GEOCORP, INC. PointMan is a trademark of PROSTAR GEOCORP, INC. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. and any use of such marks by Radiodetection Ltd. is under license. Google Earth is a trademark of Google LLC. Appearance and specifications of third-party products are subject to change without notice. The use of a third-party's image and/or trademark in this brochure does not imply any sponsorship, affiliation with or endorsement by the rights holder. *The positioning performance described reflects typical capabilities of high-accuracy GNSS solutions. Standards and specification materials covering geodetic control and professional GNSS surveys include accuracy classifications that range from sub-centimeter up to about 10 cm at typical confidence levels (e.g., 95%) for professional work. Actual results may vary based on field conditions, GNSS signal quality, availability of correction sources (e.g., RTK or SBAS), environmental factors (e.g., multipath, canopy, urban canyons), and how the equipment is deployed and operated. This document may not be copied, reproduced, transmitted, modified or used, in whole or in part, without the prior written consent of Radiodetection Ltd. Photos are indicative and products received may not be identical to those shown.

CONTACT US

DIP-2026-00059-00